

7227000


Single Band | Shrouded Yagi | V / H-Pol | 26° | 17.0 dBd

- Shrouded Yagi antenna available for SHF Links in the 1.4 GHz band
- All elements enclosed in a weather resistant, glassfibre shroud
- Able to provide consistent, reliable performance in all weather conditions




Electrical Characteristics			
Frequency Band	1427-1530 MHz		
Polarization	Vertical or Horizontal		
Horizontal Beamwidth	26°		
Vertical Beamwidth	25°		
Gain	17.0 dBd		
Impedance	50Ω		
VSWR	<1.3:1		
Front-to-Back Ratio	> 25 dB		
Power Rating	100 W		
Lightning Protection	DC Grounded		
Connector(s)	N-Female		
Mechanical Characteristics			
Materials	Shroud	GRP	
	Radiating Assembly	Aluminum	
	Mounting Section (diameter)	Aluminum, 50 mm (1.9 in) diameter	
Dimensions (Length)	1360 mm	53.5 in	
Weight without Mounting Bracket	3.0 kg	6.6 lbs	
Wind Load (160 km/hr or 100 mph)	150 N	33.7 lbf	
Mounting Options		Part Number	
Mounting brackets are ordered separately.			
Mounting Bracket	3202078/68		
Alternate Mounting Bracket	0300064/00 + U-bolts to match mounting pipe diameter		

1427-1530 MHz



Horizontal



Vertical

Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.