

## PDU2F1V1

### 6-Way Power Distribution Unit

Technical Characteristics		
Input Port	DC -48V ± 1V	
Output Port	DC 12V ± 1V	
Functions	Working Status Indicator Over Current Alarm Low Current Alarm Bypass Alarm Abnormity Bypass Reset	
Input Voltage	-40V to 60V	
Output Voltage	12V ± 1V	
Output Current	12mA ± 20mA	
Low Current Alarm Current	< 60mA	
Over Current Alarm Current	> 200mA	
Size	1U 19 inch standard insert drawer	
Environmental Characteristics		
Operating Temperature	-20° to +55° C	-4° to +131° F
Storage Temperature	-45° to +60° C	-49° to +140° F
Relative Humidity (non-condensation)	≤ 95%	
Mechanical Characteristics		
Dimensions - Body (Height x Width x Depth)	500 x 210 x 50 mm	19.7 x 8.3 x 2.0 in
Packing Dimensions (HxWxD)	580 x 260 x 100 mm	22.8 x 10.2 x 3.9 in
Net Weight	3.1 kg	6.8 lbs
Gross Weight	4.5 kg	9.9 lbs

Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.