

2C2UT070X06Fxs1

QUAD BAND | DIPLEXED | 3-SECTOR, CLOVER-SHAPE | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Features

- Diplexed, 3-Sector, Clover-Shape configuration with 12 connectors
- Ideal for Small Cell / DAS applications
- Available with 4.3-10 connectors
- Four unique mounting options
- Available for order with a grey, brown or black radome



Connector Description

The antenna has 12 connectors located at the bottom.

Low Band #1	■ R1	696-960 MHz	(3x) 4.3-10 Female
Low Band #2	■ R2	696-960 MHz	(3x) 4.3-10 Female
Mid Band #1	■ Y1	1695-2700 MHz	(3x) 4.3-10 Female
Mid Band #2	■ Y2	1695-2700 MHz	(3x) 4.3-10 Female

Electrical Characteristics	■ R1 ■ R2		■ Y1 ■ Y2			
	(2x) 696-960 MHz		(2x) 1695-2700 MHz			
Frequency Bands (MHz)	696-806	806-960	1695-1880	1850-1990	1920-2200	2300-2700
Polarization	(2x) ±45°		(2x) ±45°			
Horizontal Beamwidth	75°	70°	75°	76°	77°	63°
Vertical Beamwidth	80°	54°	17°	16°	15°	14°
Gain	6.7 dBi	6.3 dBi	12.3 dBi	12.7 dBi	13.0 dBi	13.2 dBi
Electrical Downtilt (°)	(x) 0		(y) 0, 6			
Impedance	50Ω		50Ω			
VSWR	≤ 1.5:1		≤ 1.5:1			
Upper Sidelobe Suppression	N/A		> 15 dB			
Front-to-Back Ratio	> 25 dB		> 20 dB			
Isolation Between Ports	23 dB		22 dB			
IM3 (2x20W carrier)	< -153 dBc		< -153 dBc			
Input Power	(6x) 500 W		(6x) 300 W			
Diplexed	Yes					
Number of Sectors, Sector Spacing and/or Pattern Shape	3 Sectors, 120° Spacing, Clover-Shape					
Lightning Protection	Direct Ground					

Mechanical Characteristics

Antenna Dimensions (Height x Diameter)	610 x 371 mm	24.0 x 14.6 in
Weight without Mounting Bracket Kit	15.9 kg	35.0 lbs
Antenna Volume	0.07 m ³	2.3 ft ³
Survival Wind Speed	241 km/hr	150 mph
Wind Area	0.22 m ²	2.4 ft ²
Wind Load (160 km/hr or 100 mph)	191 N	43 lbf

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C2UT070X06FxyS1

QUAD BAND | DIPLEXED | 3-SECTOR, CLOVER-SHAPE | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Bottom View - Labeling




Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C2UT070X06F_{xy}s1

QUAD BAND | DIPLEXED | 3-SECTOR, CLOVER-SHAPE | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Bottom View - Connector Diagram



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C2UT070X06F_{xy}s1

QUAD BAND | DIPLEXED | 3-SECTOR, CLOVER-SHAPE | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Ordering Options

When ordering, select the Radome Color and Degree of Electrical Downtilt for the Low (x) and Mid Bands (y)

Radome Color	Electrical Downtilt Degree		Model Number
	Low Band ■ R1 ■ R2 (x)	Mid Band ■ Y1 ■ Y2 (y)	
Grey Pantone 420 C	0°	0°	2C2UT070X06F00s1
	0°	6°	2C2UT070X06F06s1
Brown Pantone 476 C	0°	0°	2C2UT070X06F00s1BR
	0°	6°	2C2UT070X06F06s1BR
Black RAL 9011	0°	0°	2C2UT070X06F00s1BK
	0°	6°	2C2UT070X06F06s1BK

2C2UT070X06F_{xys}1

QUAD BAND | DIPLEXED | 3-SECTOR, CLOVER-SHAPE | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Mounting Kits

This antenna can be mounted using any of the following mounting kits. Mounting kits must be ordered separately.

Side Mounting Bracket Kit	Top Mounting Bracket Kit	Utility Pole Mounting Bracket Kit	Wide Diameter Pole Top Mounting Bracket Kit
CWT-MKS-SIDE	CWT-MKS-TOP	WB3X-MKS-01	CWT-MKS-BASE-xx
			