

## 2C2UT360X06F<sub>xys</sub>1

QUAD BAND | DIPLEXED | OMNI | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

### Features

- Diplexed, Omni configuration with 4 connectors
- Ideal for Small Cell / DAS applications
- Available with 4.3-10 connectors
- Four unique mounting options
- Available for order with a grey, brown or black radome



### Connector Description

The antenna has 4 connectors located at the bottom.

Low Band ■ R1 / Mid Band ■ Y1 696-960 / 1695-2700 MHz (2x) 4.3-10 Female Connectors

Low Band ■ R2 / Mid Band ■ Y2 696-960 / 1695-2700 MHz (2x) 4.3-10 Female Connectors

Electrical Characteristics	<span style="color: red;">■</span> R1 <span style="color: red;">■</span> R2		<span style="color: yellow;">■</span> Y1 <span style="color: yellow;">■</span> Y2			
	(2x) 696-960 MHz		(2x) 1695-2700 MHz			
Frequency Bands (MHz)	696-806	806-960	1695-1880	1850-1990	1920-2200	2300-2700
Polarization	(2x) ±45°		(2x) ±45°			
Horizontal Beamwidth	360°	360°	360°	360°	360°	360°
Vertical Beamwidth	60°	55°	17°	16°	15°	14°
Gain	2.1 dBi	3.3 dBi	8.2 dBi	8.1 dBi	8.3 dBi	8.4 dBi
Electrical Downtilt (°)	(x) 0		(y) 0, 6			
Impedance	50Ω		50Ω			
VSWR	≤ 1.5:1		≤ 1.5:1			
Upper Sidelobe Suppression	> 15 dB		> 15 dB			
Isolation Between Ports	20 dB		25 dB			
IM3 (2x20W carrier)	< -153 dBc		< -153 dBc			
Input Power	(4x) 300 W					
Diplexed	Yes					
Number of Sectors, Sector Spacing and/or Pattern Shape	Omni					
Lightning Protection	Direct Ground					

### Mechanical Characteristics

Antenna Dimensions (Height x Diameter)	610 x 371 mm	24.0 x 14.6 in
Weight without Mounting Bracket Kit	10.4 kg	23 lbs
Antenna Volume	0.07 m <sup>3</sup>	2.3 ft <sup>3</sup>
Survival Wind Speed	241 km/hr	150 mph
Wind Area	0.22 m <sup>2</sup>	2.4 ft <sup>2</sup>
Wind Load (160 km/hr or 100 mph)	191 N	43 lbf

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 2C2UT360X06F<sub>xy</sub>s1

QUAD BAND | DIPLEXED | OMNI | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

### Bottom View - Labeling



2C2UT360X06F<sub>xy</sub>s1

QUAD BAND | DIPLEXED | OMNI | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

Bottom View - Connector Diagram

**NO  
IMAGE  
AVAILABLE**

**COMING  
SOON**

## 2C2UT360X06F<sub>xys</sub>1

QUAD BAND | DIPLEXED | OMNI | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

### Ordering Options

When ordering, select the Radome Color and Degree of Electrical Downtilt for the Low (x) and Mid Bands (y)

Radome Color	Electrical Downtilt Degree		Model Number
	Low Band ■ R1 ■ R2 (x)	Mid Band ■ Y1 ■ Y2 (y)	
Grey Pantone 420 C	0°	0°	2C2UT360X06F00s1
	0°	6°	2C2UT360X06F06s1
Brown Pantone 476 C	0°	0°	2C2UT360X06F00s1BR
	0°	6°	2C2UT360X06F06s1BR
Black RAL 9011	0°	0°	2C2UT360X06F00s1BK
	0°	6°	2C2UT360X06F06s1BK

## 2C2UT360X06F<sub>xys</sub>1

QUAD BAND | DIPLEXED | OMNI | CANISTER ANTENNA | X-POL | FIXED TILT | 610 MM (24.0 IN)

### Mounting Kits

This antenna can be mounted using any of the following mounting kits. Mounting kits must be ordered separately.

Side Mounting Bracket Kit	Top Mounting Bracket Kit	Utility Pole Mounting Bracket Kit	Wide Diameter Pole Top Mounting Bracket Kit
CWT-MKS-SIDE	CWT-MKS-TOP	WB3X-MKS-01	CWT-MKS-BASE-xx
			