


5088000A

Multi Band | Indoor Omni | Linear-Pol | 360° | 2.5-5.0 dBi

- Indoor, wideband, omni-directional antenna
- Distribution of GSM/CDMA/WIFI/3G/LTE 5 G Services
- Compact, light weight and easy to install



Ordering Options		Model Number			
Antenna with N Female Connectors		5088000A			
Antenna with 4.3-10 Female Connectors		5088000A-4310			
Electrical Characteristics					
Frequency Band	698-960 MHz	1427-1710 MHz	1710-2700 MHz	3400-3800 MHz	
Polarization	(2x) Linear				
Gain	2.5 ± 1.0 dBi	4.0 ± 1.0 dBi	4.5 ± 1.0 dBi	5.0 ± 1.0 dBi	
Impedance	50Ω				
VSWR	≤ 1.8				
Intermodulation IM3 (2x20W)	≤ -153 dBc				
Input Power	50W				
Connector(s)	2 Connectors / 4.3-10 or N Female				
Mechanical Characteristics					
Radome Material / Color	ABS / White, RAL9003				
Dimensions (Diameter x Height)	290 x 140 x 18 mm (11.4 x 5.5 x 0.71 in)				
Weight without Mounting Brackets	0.4 kg (0.88 lbs)				
Environmental Characteristics					
Operational Temperature	-55° to 60° C (-67° to +140° F)				
Operational Humidity	< 95 %				
Mounting Characteristics					
Mounting	Ceiling, Via Hole (standard)				

Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.