

5968400P


5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm



- Twin tri band antenna, dual polarisation, 10 connectors
- Independent tilt on each band 2-12° / 2-12° / 2-12° / 2-12° / 2-12°
- Lightweight Twin+™, next generation TwinLine™ platform and low windload
- MET and RET versions, 3GPP/AISG2.0, in multiple single RET (multiple device type1) or in Multi-RET (device type 17, with firmware above MD3.10).
- Our patented, RET module controlling all tilt angles, fully inserted inside the antenna (field replaceable)

PRODUCT OVERVIEW	Frequency Range (MHz)	698-960	698-960	1427-2180	1427-2690	2490-2690
	Array	■ R1	■ R2	■ B1	■ Y1	■ Y2
	Connector	1-2	3-4	5-6	7-8	9-10
	Polarization	XPOL	XPOL	XPOL	XPOL	XPOL
	Azimuth Beamwidth (avg)	65°	65°	65°	65°	65°
	Electrical Downtilt	2-12°	2-12°	2-12°	2-12°	2-12°
	Dimensions	1915 x 432 x 175 mm				



ORDERING OPTIONS

Select from the different options listed below

SELECT ELECTRICAL DOWNTILT CONTROL & AISG PROTOCOL	SELECT ACTUATOR	SELECT CONNECTOR TYPE	ANTENNA MODEL NUMBER
Manual Electrical Tilt (MET)	---	4.3-10 Female	5968400P
Remote Electrical Tilt (RET) AISG v2.0 / 3GPP	Multi-Device Control Unit (MDCU)	4.3-10 Female	5968400PG
	Multi-Device Dual Unit (MDDU)	4.3-10 Female	5968400PDx*

*Pre-commissioned configuration; Contact Amphenol for further details.



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm

ELECTRICAL SPECIFICATIONS Ultra Low Band

■ R1

Frequency Range		MHz	698-960		
		MHz	698-806	790-862	880-960
Polarization		---	±45°		
Gain	Over all Tilts	dBi	14.4 ± 0.6	15.0 ± 0.4	15.5 ± 0.5
Azimuth Beamwidth		degrees	71.2° ± 5.5°	68.3° ± 5.7°	64.7° ± 5.4°
Elevation Beamwidth		degrees	11.8° ± 1.6°	10.5° ± 0.8°	9.5° ± 0.6°
Electrical Downtilt		degrees	2°-12°		
Impedance		Ohms	50		
VSWR		---	< 1.5		
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110		
Front-to-Back Ratio, Total Power, ±30°		dB	> 23.3	> 24.1	> 23.6
Upper Sidelobe Suppression, 0° to 20°		dB	> 13.3	> 15.4	> 16.6
Maximum Effective Power Per Port		Watts	250 W		
Inter/Intra Band Isolation		dB	> 25		

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

ELECTRICAL SPECIFICATIONS Ultra Low Band

■ R2

Frequency Range		MHz	698-960		
		MHz	698-806	790-862	880-960
Polarization		---	±45°		
Gain	Over all Tilts	dBi	14.4 ± 0.6	15.0 ± 0.4	15.5 ± 0.5
Azimuth Beamwidth		degrees	71.2° ± 5.5°	68.3° ± 5.7°	64.7° ± 5.4°
Elevation Beamwidth		degrees	11.8° ± 1.6°	10.5° ± 0.8°	9.5° ± 0.6°
Electrical Downtilt		degrees	2°-12°		
Impedance		Ohms	50		
VSWR		---	< 1.5		
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110		
Front-to-Back Ratio, Total Power, ±30°		dB	> 23.3	> 24.1	> 23.6
Upper Sidelobe Suppression, 0° to 20°		dB	> 13.3	> 15.4	> 16.6
Maximum Effective Power Per Port		Watts	250 W		
Inter/Intra Band Isolation		dB	> 25		

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm

ELECTRICAL SPECIFICATIONS Filtered Array (Y2)

■ B1

Frequency Range		MHz	1427-2180		
		MHz	1427-1518	1695-1920	1920-2180
Polarization		---	±45°		
Gain	Over all Tilts	dBi	15.0 ± 0.2	16.5 ± 0.5	16.9 ± 0.5
Azimuth Beamwidth		degrees	66.4° ± 4.7°	69.4° ± 4.7°	62.8° ± 5.8°
Elevation Beamwidth		degrees	8.7° ± 0.5°	7.1° ± 0.3°	6.2° ± 0.6°
Electrical Downtilt		degrees	2°-12°		
Impedance		Ohms	50		
VSWR		---	< 1.5		
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110		
Front-to-Back Ratio, Total Power, ±30°		dB	> 27.7	> 30.2	> 32.9
Upper Sidelobe Suppression, 0° to 20°		dB	> 14.0	> 17.1	> 18.2
Maximum Effective Power Per Port		Watts	200 W		
Inter/Intra Band Isolation		dB	> 28		

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

ELECTRICAL SPECIFICATIONS MEGA Wide Band

■ Y1

Frequency Range		MHz	1427-2690					
		MHz	1427-1518	1695-1880	1850-1990	1920-2180	2300-2500	2490-2690
Polarization		---	±45°					
Gain	Over all Tilts	dBi	15.9 ± 0.2	16.7 ± 0.4	17.0 ± 0.3	17.3 ± 0.4	17.1 ± 0.4	17.3 ± 0.6
Azimuth Beamwidth		degrees	65.7° ± 4.9°	69.9° ± 4.8°	66.5° ± 2.6°	62.9° ± 6.0°	64.3° ± 4.9°	60.9° ± 6.1°
Elevation Beamwidth		degrees	8.6° ± 0.3°	7.1° ± 0.3°	6.7° ± 0.3°	6.2° ± 0.6°	5.3° ± 0.2°	4.8° ± 0.4°
Electrical Downtilt		degrees	2°-12°					
Impedance		Ohms	50					
VSWR		---	< 1.5					
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110					
Front-to-Back Ratio, Total Power, ±30°		dB	> 27.5	> 30.2	> 32.0	> 33.2	> 27.3	> 28.4
Upper Sidelobe Suppression, Peak to 20°		dB	> 13.8	> 18.0	> 19.2	> 18.3	> 16.3	> 15.2
Cross Polar Ratio - Main Direction (0°)		dB	> 17.5	> 18.3	> 18.1	> 17.1	> 20.3	> 15.7
Maximum Effective Power Per Port		Watts	200 W					
Inter/Intra Band Isolation		dB	> 25					

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm

ELECTRICAL SPECIFICATIONS Filtered Array (B1)

■ Y2

Frequency Range		MHz	2490-2690
		MHz	2490-2690
Polarization		---	±45°
Gain	Over all Tilts	dBi	17.0 ± 0.5
Azimuth Beamwidth		degrees	60.1° ± 6.2°
Elevation Beamwidth		degrees	4.9° ± 0.4°
Electrical Downtilt		degrees	2°-12°
Impedance		Ohms	50
VSWR		---	< 1.5
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110
Front-to-Back Ratio, Total Power, ±30°		dB	> 28.8
Upper Sidelobe Suppression, 0° to 20°		dB	> 14.6
Maximum Effective Power Per Port		Watts	200 W
Inter/Intra Band Isolation		dB	> 25

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm

ELECTRICAL DOWNTILT CONTROL

For multiband antennas, electrical downtilt for each band can be controlled separately.

Manual Electrical Tilt (MET) Control	A colored knob at the end of the tilt indicator allows change of the tilt without need of a tool. The knob color is identical to the corresponding connector color. The manual tilt 'override' function is always available with no need to remove the physical RET motor.
Remote Electrical Tilt (RET) Control	The remote control of the electrical tilt is managed by a Multi-Device Control Unit (MDCU) or a Multi-Device Dual Unit (MDDU) inserted in the bottom of the antenna. <i>See details below and refer to the ordering options to see which actuators are available with this particular antenna.</i> A single actuator individually controls the tilt of each band (no need for daisy chain cables between the bands). This module does not add any additional length to the antenna.

RET ACTUATOR

Amphenol's **RET-READY** antennas are delivered with the RET Actuator already installed and pre-commissioned with all antenna parameters. Every RET device is factory configured and calibrated so the antenna is ready to be used once delivered to the site which means that there is no need for further installation of RET devices or for programming their configuration or for running a calibration process.



RET-READY ACTUATORS	Multi-Device Control Unit (MDCU). The MDCU is an electronic module that allows the remote control of the electrical downtilt (RET) in Amphenol antennas with factory embedded motors. The MDCU is factory installed and has two male AISG 8 pin connectors (type IEC60130-9 Ed 3.0). <i>Refer to the ORDERING OPTIONS for availability with this model</i>	
	Multi-Device Dual Unit (MDDU). The MDDU allows two separate RET Controllers to independently drive the RETs in antennas with factory embedded motors (for antenna sharing or two technologies). The MDDU is factory installed and has one pair of AISG Male and Female connectors (type IEC60130-9). <i>Refer to the ORDERING OPTIONS for availability with this model.</i>	
Number of RET-READY Actuators	One per antenna	
Input Voltage	+10 to +30 V	
Power Consumption	Idle State (AISG P1)	0.5 W
	High Power Mode (AISG P2)	3 W
Protocol	3GPP/AISG 2.0	
Tilt Change Duration	Less than 15 seconds, typical (may vary dependent on antenna type and outdoor temperature)	
Precision	±0.5°	
Tilt Change Capability	50,000 minimum	
Field Replaceable Unit	Yes	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm



ARRAY LAYOUT	ARRAY	FREQUENCY	CONNECTOR	CONNECTOR TYPE
	R1	698-960	1-2	4.3-10 Female
	R2	698-960	3-4	4.3-10 Female
	B1	1427-2180	5-6	4.3-10 Female
	Y1	1427-2690	7-8	4.3-10 Female
	Y2	2490-2690	9-10	4.3-10 Female

Diagram shown at right depicts the view from the front of the antenna. The illustration is not shown to scale.

MECHANICAL SPECIFICATIONS

Length	mm (in)	1915 (75.4)	
Width	mm (in)	432 (17.0)	
Depth	mm (in)	175 (6.9)	
Net Weight - Antenna Only	kg (lbs)	40 (88.2)	
Mechanical Distance Between Mounting Points	mm (in)	Refer to Diagram	
Windload	Calculation	km/h (mph)	150 (93.2)
	Frontal	N (lbf)	635 (142.8)
	Lateral	N (lbf)	395 (88.8)
	Rearside	N (lbf)	656 (147.5)
Operational Wind Speed	km/h (mph)	160 (99.4)	
Survival Wind Speed	km/h (mph)	200 (124)	
Radome Color	---	Gray RAL7035	
Radome Material	---	Outdoor Fiberglass	
Lightning Protection	---	Direct Ground	
Shipping	Shipping Dimensions (Length x Width x Depth)	mm (in)	2150 x 500 x 340 (84.6 x 19.7 x 13.4)
	Shipping Weight	kg (lbs)	51 (112.4)
	Shipping Volume	m ³ (ft ³)	0.37 (13.1)

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

5968400P

5968400PG 5968400PDx

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1915 mm

ENVIRONMENTAL SPECIFICATIONS

Environmental Standard	---	ETS 300 019
Operating Temperature	° C (° F)	-40° to +60° (-40° to 140°)
Product Environmental Compliance	---	Product is RoHs Compliant

ACCESSORIES

All accessories are ordered separately unless otherwise indicated

ITEM	MODEL NUMBER	WEIGHT
Brackets for pole Ø48 to Ø115 mm (Ø1.9 to Ø4.5 in) delivered as standard	0900181/00	3.4 kg (7.5 lbs)
Brackets for pole Ø70 to Ø150 mm (Ø2.8-Ø5.9 in) optional	0900182/00	3.9 kg (8.6 lbs)
Kit to add mechanical tilt (0° to 10°) to above brackets optional	0900396/00	2.3 kg (5.1 lbs)


INSTALLATION

Please read all installation notes before installing this product.



Always attach the antenna but all mounting points.

Do not install the antenna with the connectors facing upwards.



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.