

6176100

6176100G

1-Band, 2-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1404 mm

- Single band antenna, dual polarisation, 2 connectors
- Variable electrical tilt 0-12°
- MET and RET versions, 3GPP/AISG2.0
- Single RET module to control all tilt angles, fully inserted inside the antenna (field replaceable)

PRODUCT OVERVIEW	Frequency Range (MHz)	1710-2690
	Array	Y1
	Connector	1-2
	Polarization	XPOL
	Azimuth Beamwidth (avg)	65°
	Electrical Downtilt	0-12°
	Dimensions	1404 x 155 x 75 mm



ORDERING OPTIONS

Select from the different options listed below

SELECT ELECTRICAL DOWNTILT CONTROL & AISG PROTOCOL	SELECT ACTUATOR	SELECT CONNECTOR TYPE	ANTENNA MODEL NUMBER
Manual Electrical Tilt (MET)	---	7/16-DIN Female	6176100
Remote Electrical Tilt (RET) AISG v2.0 / 3GPP	Multi-Device Control Unit (MDCU)	7/16-DIN Female	6176100G



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

6176100

6176100G

1-Band, 2-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1404 mm

ELECTRICAL SPECIFICATIONS Ultra Wide Band

Y1

Frequency Range		MHz	1710-2690				
		MHz	1710-1880	1850-1990	1920-2180	2300-2500	2490-2690
Polarization		---	±45°				
Gain	Over all Tilts	dBi	15.5 ± 0.1	15.7 ± 0.2	16.3 ± 0.6	18.2 ± 0.2	17.8 ± 0.3
Azimuth Beamwidth		degrees	74.4° ± 2.4°	75.3° ± 2.8°	73.5° ± 5.5°	62.9° ± 2.8°	62.1° ± 2.0°
Elevation Beamwidth		degrees	8.1° ± 0.6°	7.3° ± 0.6°	6.6° ± 0.6°	5.5° ± 0.4°	5.3° ± 0.3°
Electrical Downtilt		degrees	0°-12°				
Impedance		Ohms	50				
VSWR		---	< 1.5				
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110				
Front-to-Back Ratio, Total Power, ±30°		dB	> 27.2	> 25.6	> 24.5	> 28.7	> 29.4
Upper Sidelobe Suppression, Peak to 20°		dB	> 18.9	> 18.5	> 17.9	> 17.2	> 16.3
Cross Polar Ratio - Main Direction (0°)		dB	> 25.2	> 23.3	> 21.0	> 17.8	> 16.3
Maximum Effective Power Per Port		Watts	250 W				
Inter/Intra Band Isolation		dB	> 28				

Standard values based on NGMN-P-BASTA version 9.6 recommendation.

ELECTRICAL DOWNTILT CONTROL

For multiband antennas, electrical downtilt for each band can be controlled separately. Tilt indicator(s) are covered by removable transparent cap(s).

Manual Electrical Tilt (MET) Control	A colored knob at the end of the tilt indicator allows change of the tilt without need of a tool. The knob color is identical to the corresponding connector color. To access the knob, remove the cap by turning it counter-clockwise. It is re-installed by opposite rotation. Do not remove the transparent cap(s) from the antenna.
Remote Electrical Tilt (RET) Control	The remote control of the electrical tilt is managed by a Multi-Device Control Unit (MDCU) inserted in the bottom of the antenna. See details below and refer to the ordering options to see which actuators are available with this particular antenna. A single actuator individually controls the tilt of each band (no need for daisy chain cables between the bands). This module does not add any additional length to the antenna. For RET control, the transparent caps must be in place and locked. The tilt angle indicators always remain visible and the antenna still has manual tilt control (manual override). Do not remove the transparent cap(s) from the antenna.

RET ACTUATOR

Amphenol's **RET-READY** antennas are delivered with the RET Actuator already installed and pre-commissioned with all antenna parameters. Every RET device is factory configured and calibrated so the antenna is ready to be used once delivered to the site which means that there is no need for further installation of RET devices or for programming their configuration or for running a calibration process.

RET-READY ACTUATORS	Multi-Device Control Unit (MDCU). The MDCU is an electronic module that allows the remote control of the electrical downtilt (RET) in Amphenol antennas with factory embedded motors. The MDCU is factory installed. Refer to the ORDERING OPTIONS for availability with this model	
Number of RET-READY Actuators		One per antenna
Input Voltage		+10 to +30 V
Power Consumption	Idle State	0.5 W
	Operating	4 W typical / 10 W maximum
Protocol		3GPP/AISG 2.0
Tilt Change Duration		Less than 15 seconds, typical (may vary dependent on antenna type and outdoor temperature)
Precision		±0.5°
Tilt Change Capability		50,000 minimum
RET Interface		1 pair of AISG Male and Female (type IEC60130-9)
Field Replaceable Unit		Yes

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

6176100

6176100G

1-Band, 2-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1404 mm



ARRAY LAYOUT	ARRAY	FREQUENCY	CONNECTOR	CONNECTOR TYPE
	Y1	1710-2690	1-2	7/16-DIN Female Long Neck




Diagram shown at right depicts the view from the front of the antenna.
The illustration is not shown to scale.

MECHANICAL SPECIFICATIONS

Length		mm (in)	1404 (55.3)
Width		mm (in)	155 (6.1)
Depth		mm (in)	75 (3.0)
Net Weight - Antenna Only		kg (lbs)	4.5 (9.9)
Mechanical Distance Between Mounting Points		mm (in)	Refer to Diagram
Windload (Wind Tunnel Coefficients)	Calculation	km/h (mph)	150 (93.2)
	Frontal	N (lbf)	276 (62.0)
	Lateral	N (lbf)	125 (28.1)
	Rearside	N (lbf)	173 (38.9)
Operational Wind Speed		km/h (mph)	160 (99.4)
Survival Wind Speed		km/h (mph)	200 (124)
Radome Color		---	Gray RAL7035
Radome Material		---	Outdoor Fibreglass
Lightning Protection		---	Direct Ground

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

6176100

6176100G

1-Band, 2-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 1404 mm

ENVIRONMENTAL SPECIFICATIONS

Environmental Standard	---	ETS 300 019
Operating Temperature	° C (° F)	-40° to +60° (-40° to 140°)
Product Environmental Compliance	---	Product is RoHs Compliant

ACCESSORIES

 All accessories are ordered separately unless otherwise indicated

ITEM	MODEL NUMBER	WEIGHT
Brackets for pole Ø48 to Ø115 mm (Ø1.9 to Ø4.5 in) delivered as standard	0900181/00	3.4 kg (7.5 lbs)
Brackets for pole Ø70 to Ø150 mm (Ø2.8-Ø5.9 in) optional	0900182/00	3.9 kg (8.6 lbs)
Kit to add mechanical tilt (0° to 10°) to above brackets optional	0900397/00	3.0 kg (6.6 lbs)

Wall mounting brackets are available upon request

INSTALLATION


 Please read all installation notes before installing this product.


Always attach the antenna by all mounting points.

Do not install the antenna with the connectors facing upwards.

Do not cut the tethered transparent caps(s) that cover the antenna's tilt adjustment indicators.

In order to operate the RET control, the transparent caps covering the tilt adjustment indicators must be engaged and locked.



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.