


7042410


Single Band | 6-Element Yagi | V-Pol or H-Pol | 64° | 8.5 dBd

- Antenna for PMR/Trunked Radio, Broadcast and Tetra applications
- Robust antenna design ensures reliable operation in harsh environmental conditions

Electrical Characteristics			
Frequency Band	380-430 MHz		
Bandwidth	±6% (typical)		
Polarization	Vertical or Horizontal		
Horizontal Beamwidth	64°		
Vertical Beamwidth	50°		
Gain	8.5 dBd		
Impedance	50Ω		
VSWR	< 1.5:1		
Front-to-Back Ratio	15 dB max (typically better than 18 dB)		
Power Rating	150 W		
Connector Type	N Female + 3m of RG213 cable		
Lightning Protection	DC Grounded		
Mechanical Characteristics			
Materials	Boom	32 mm diameter; Aluminum	
	Elements	12.7 mm diameter; Aluminum	
	Balun	Fully moulded enclosure	
Dimensions (Length)	1103 mm	43.4 in	
Weight without Mounting Brackets	3 kg	6.6 lbs	
Wind Load @ 160 km/hr (100 mph)	94 N	21.1 lbf	
Mounting Options			
Mounting bracket kits are ordered separately.			
Mounting Bracket Kit	3202078/68 + 3201079/00		
Alternate Mounting Brackets	0900912/00 + U-bolts to match mounting pipe diameter		
	0302032/68 + U-bolts to match mounting pipe diameter		
	0300064/00 + U-bolts to match mounting pipe diameter		



Horizontal



0° | Vertical

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.