


## 7160860


## V-Pol | Yagi | 42° | 13.2 dBi

| Electrical Characteristics      |   |         |
|---------------------------------|---|---------|
| Frequency band                  | 824-896 MHz   |         |
| Polarization                    | Vertical  |         |
| Horizontal beamwidth            | 42°   |         |
| Vertical beamwidth              | 38°   |         |
| Gain                            | 11.1 dBd / 13.2 dBi   |         |
| VSWR                            | <1.35:1   |         |
| Front-to-back ratio             | >20 dB  |         |
| Input power                     | 150 W   |         |
| Connector type / Location       | N-Female / Rear of Shroud   |         |
| Mechanical Characteristics      |   |         |
| Dimensions (Length)             | 1080 mm   | 42.5 in |
| Weight without bracket          | 2.9 kg  | 6.3 lbs |
| Suvival wind speed              | 200 km/hr   | 125 mph |
| Wind load @ 160 km/hr (100 mph) | 124 N   | 28 lbf  |
| Mounting Options                | Part Number   |         |
| Mounting bracket                | 99284 + U-bolts to match mounting pipe diameter<br>Available U-bolts: UB03 (2-inch), UB06 (3-inch), UB07 (4-inch) |         |



Please order Mounting Bracket separately.





Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.