

A-002xxDHyyzz-CC

2W Attenuator | Indoor Use

This model was previously released as AA-002-xx-DH-yyzz-CC



Electrical Characteristics						
Frequency Range	DC-3 GHz					
VSWR	≤ 1.20					
Power	2 W					
Attenuation Value (xx)	3 dB	6 dB	10 dB	15 dB	20 dB	30 dB
Accuracy	≤ 0.3 dB	≤ 0.5 dB	≤ 0.7 dB	≤ 0.8 dB	≤ 0.8 dB	≤ 1.0 dB
PIM	≤ -110 dBc					
Impedance	50Ω					
Mechanical Characteristics						
Dimensions without connectors	58 x Ø20 mm					
Weight	0.064 kg					
Connector Type	See Ordering Options Below					
Environmental Characteristics						
Application	Indoor					
Operating Temperature	-55° C to +85° C					

Ordering Options

When ordering, select the Attenuation Value (xx), then select the Connector Type (yyzz).

Attenuation Value	Connector Type (yyzz)		
	N Male to N Female	4.3/10 Male to 4.3/10 Female	7/16-DIN Male to 7/16-DIN Female
3 dB (03)	A-00203DHNMNF-CC	A-00203DH4M4F-CC	A-00203DHD MDF-CC
6 dB (06)	A-00206DHNMNF-CC	A-00206DH4M4F-CC	A-00206DHD MDF-CC
10 dB (10)	A-00210DHNMNF-CC	A-00210DH4M4F-CC	A-00210DHD MDF-CC
15 dB (15)	A-00215DHNMNF-CC	A-00215DH4M4F-CC	A-00215DHD MDF-CC
20 dB (20)	A-00220DHNMNF-CC	A-00220DH4M4F-CC	A-00220DHD MDF-CC
30 dB (30)	A-00230DHNMNF-CC	A-00230DH4M4F-CC	A-00230DHD MDF-CC

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

A-002xxDHyyzz-CC

2W Attenuator | Indoor Use

Dimensional Drawings

A-002xxDHNMF-CC

