

APS-xx-WBL-LP-NF-CC

Power Splitter | N Female | Square Body

Ordering Options		2-Way Splitter	3-Way Splitter
Model Number (xx)		APS-02-WBL-LP-NF-CC	APS-03-WBL-LP-NF-CC
			
Electrical Characteristics			
Frequency Range		350-2700 MHz	350-2700 MHz
VSWR		≤ 1.25	≤ 1.30
Power Rating		300 W	350 W
PIM3 (2x43 dBm)		≤ -153 dBc	≤ -153 dBc
Insertion Loss		0.22 dB	0.3 dB
Split Loss		3 dB	4.8 dB
Peak Power (max)		1.5 kW	1.5 kW
Impedance		50Ω	50Ω
Mechanical Characteristics			
Plating	Inner Contact	Silver	Silver
	Outer Trimetal	Trimetal	Trimetal
Connector		N Female	N Female
Environmental Characteristics			
Operating Temperature		-30° C to +75° C (-22° F to +167° F)	-30° C to +75° C (-22° F to +167° F)
Relative Humidity		Up to 95%	Up to 95%
RoHS Compliant		yes	yes
Application		Indoor / Outdoor	Indoor / Outdoor
Environmental		IP65	IP65


Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

APS-xx-WBL-LP-NF-CC


Power Splitter | N Female | Square Body

Dimensional Drawings

APS-02-WBL-LP-NF-CC



APS-03-WBL-LP-NF-CC



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.