

BXA-70063-8CF-EDIN-X

Single Band | Panel Antenna | X-Pol | 63° | 18.1 dBi | Fixed Tilt

- Single band, panel antenna with fixed electrical tilt





Ordering Options		
When ordering, replace the "X" in the model number with the electrical downtilt. Select from the options listed in the Electrical Downtilt section below.		
Electrical Characteristics		696-900 MHz
Frequency Bands	696-806 MHz	806-900 MHz
Polarization	±45°	
Horizontal Beamwidth	65°	63°
Vertical Beamwidth	9°	7°
Gain	17.6 dBi	18.1 dBi
Electrical Downtilt	(X) 0, 2, 5	
Impedance	50Ω	
IM3 (2x20W carrier)	-147 dBc	
Upper Sidelobe Suppression (0°)	-16.2 dB	-19.0 dB
Front-to-Back Ratio (±30°)	-32.9 dB	-31.3 dB
VSWR	1.5:1	
Null Fill	5% (-26.02 dB)	
Isolation Between Ports	20 dB	
Input Power	500 W	
Total Number of Connectors	Antenna has 2 connectors located on the center (back) of the antenna	
Connectors Per Band	696-900 MHz	2 Connectors, Elongated 7/16-DIN Female (EDIN)
Lightning Protection	Direct Ground	
Mechanical Characteristics		
Dimensions (Length x Width x Depth)	2405 x 285 x 132 mm	94.7 x 11.2 x 5.2 in
Depth with z-brackets	170 mm	6.7 in
Weight without Mounting Brackets	10.9 kg	24 lbs
Wind Area	Front	0.69 m ² 7.4 ft ²
	Side	0.32 m ² 3.4 ft ²
Survival Wind Speed	> 201 km/hr	> 125 mph
Wind Load (161 km/hr or 100 mph)	Front	985 N 221 lbf
	Side	525 N 118 lbf

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

BXA-70063-8CF-EDIN-X

Single Band | Panel Antenna | X-Pol | 63° | 18.1 dBi | Fixed Tilt

Mounting Options	Part Number	Image	Fits Pipe Diameter	Weight
All mounting bracket kits are ordered separately unless otherwise indicated. Select from the options listed below.				
3-Point Mounting and Downtilt Bracket Kit	36210008		40-115 mm 1.57-4.5 in	6.9 kg 15.2 lbs



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.