

DPX-26x-JJ

Diplexer | PCS/AWS | Single and Twin Units | Indoor / Outdoor

- Combines 1850-2000 MHz and 1695-1780+2110-2360 MHz bands into a single output
- Usable at the BTS or antenna end
- Built in lightning protection on all ports
- Available as single or twin unit, with various DC/AISG bypass configurations
- Suitable for indoor or outdoor applications
- Pole or wall mounting



Ordering Options	Single Unit		Twin Unit	
	7/16-DIN Female Connectors	4.3-10 Female Connectors	7/16-DIN Female Connectors	4.3-10 Female Connectors

When ordering replace "x" with correct option for bypass configuration and single or twin unit.

DC/AISG bypass PCS port	DPX-263-JJ	DPX-263-JJ-43F	DPX-264-JJ	DPX-264-JJ-43F
DC/AISG bypass AWS port	DPX-261-JJ	DPX-261-JJ-43F	DPX-262-JJ	DPX-262-JJ-43F
Full DC/AISG bypass	DPX-265-JJ	DPX-265-JJ-43F	DPX-266-JJ	DPX-266-JJ-43F

Electrical Characteristics	
PCS Channel (Port 1)	
Frequency Band	1850-2000 MHz
Insertion Loss	< 0.35 dB
VSWR	< 1.25
Isolation	> 50 dB
Input Power	< 250 W
IM3, 2x43 dBm	< -117 dBm
AWS Channel (Port 2)	
Frequency Band	1695-1780 & 2110-2360 MHz
Insertion Loss	< 0.35 dB
VSWR	< 1.25
Isolation	> 50 dB
Input Power	< 250 W
IM3, 2x43 dBm	< -117 dBm
DC/AISG Transparency	
Bypass Rating	2500 mA (max)
Environmental	
Temperature Range	-40° to +65° C -40° to +149° F
Ingress Protection	IP67
Lightning Protection	10 kA 8/20 μs
Application	Indoor / Outdoor

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

DPX-26x-JJ

Diplexer | PCS/AWS | Single and Twin Units | Indoor / Outdoor

Mechanical Characteristics			
Connectors		7/16-DIN Female Long Neck or 4.3-10 Female	
Dimensions (H x W x D) Without Connectors or Mounting Brackets	Single Unit	162.5 x 140 x 48.5 mm	6.4 x 5.5 x 1.9 in
	Twin Unit	162.5 x 140 x 103 mm	6.4 x 5.5 x 4.1 in
Weight	Single Unit	2.4 kg	5.3 lbs
	Twin Unit	4.5 kg	9.9 lbs
Packing Dimensions	Single Unit	380 x 225 x 166 mm	15.0 x 8.9 x 6.5 in
	Twin Unit	380 x 225 x 220 mm	15.0 x 8.9 x 8.7 in
Mounting Options		Description	
Pole / Wall Bracket (included)		Attach to pole diameter Ø40-Ø135 mm (Ø1.57-Ø5.3 in)	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.