

QPX-54x-JJ

Quadruplexer | 690-960/1710-1880/1920-2200/2300-2700 MHz | Single and Twin Units | Indoor

- Combines four bands into a single output
- Usable at BTS or antenna end
- Built in lightning protection on all ports
- Available as single or twin unit
- Suitable for indoor or outdoor applications

**NO
IMAGE
AVAILABLE**

**COMING
SOON**

Ordering Options	Single Unit	
	7/16-DIN Female Long Neck Connector	4.3-10 Female Long Neck Connector
When ordering replace "x" with correct option for bypass configuration and single or twin unit.		
No DC/AISG bypass	QPX-540-JJ	QPX-541-JJ
Electrical Characteristics		
690-960 MHz Channel (Port 1)		
Frequency Band	690-960 MHz	
Insertion Loss	< 0.2 dB	
VSWR	< 1.25	
Isolation	> 65 dB	
Input Power	< 300 W	
IM3, 2x43 dBm	< -110 dBm	
1710-1880 MHz Channel (Port 2)		
Frequency Band	1710-1880 MHz	
Insertion Loss	< 0.4 dB	
VSWR	< 1.25	
Isolation	> 65 dB	
Input Power	< 300 W	
IM3, 2x43 dBm	< -110 dBm	
1920-2200 MHz Channel (Port 3)		
Frequency Band	1920-2200 MHz	
Insertion Loss	< 0.4 dB	
VSWR	< 1.25	
Isolation	> 65 dB	
Input Power	< 300 W	
IM3, 2x43 dBm	< -110 dBm	
2300-2700 MHz Channel (Port 4)		
Frequency Band	2300-2700 MHz	
Insertion Loss	< 0.3 dB	
VSWR	< 1.25	
Isolation	> 65 dB	
Input Power	< 300 W	
IM3, 2x43 dBm	< -110 dBm	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

QPX-54x-JJ

Quadruplexer | 690-960/1710-1880/1920-2200/2300-2700 MHz | Single and Twin Units | Indoor

Environmental Characteristics		
Operating Temperature	-40° to +65° C (-40° to 149° F)	
Application	Indoor	
IP Rating	IP65	
Mechanical Characteristics		
Connectors	7/16-DIN Female Long Neck	
Dimensions (H x W x D) Without Connectors or Mounting Brackets	210 x 180 x 40 mm	8.3 x 7.1 x 1.6 in
Weight	3.6 kg	7.9 lbs
Packing Dimensions	350 x 290 x 205 mm	13.8 x 11.4 x 8.1 in
Mounting Options		
	Description	
Wall Mounting	Bracket Included	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.