

TPX-23x-CC

Triplexer | 1710-1880 / 1920-2170 / 2500-2690 MHz | Single and Twin Units | Outdoor

- Combines 1710-1880 / 1920-2170 / 2500-2690 MHz into a single output
- Usable at BTS or antenna end
- Available as single or twin unit, with various DC/AISG bypass configurations
- Suitable for outdoor applications
- Pole or wall mounting

**NO
IMAGE
AVAILABLE**

**COMING
SOON**

Ordering Options	Single Unit	Twin Unit
When ordering replace "x" with correct option for bypass configuration and single or twin unit.		
No DC/AISG bypass	TPX-230-CC	TPX-231-CC
Electrical Characteristics		
1710-1880 MHz Channel (Port 1)		
Frequency Band	1710-1880 MHz	
Insertion Loss	≤ 0.7 dB	
Isolation	≥ 80 dB	
VSWR	≤ 1.25	
Continuous Average Power	250 W	
IM3, 2x43 dBm	< -160 dBc	
1920-2170 MHz Channel (Port 2)		
Frequency Band	1920-2170 MHz	
Insertion Loss (Port 2 to Port 4)	≤ 0.7 dB	
Isolation	≥ 80 dB	
VSWR	≤ 1.25	
Continuous Average Power	250 W	
IM3, 2x43 dBm	< -160 dBc	
2500-2690 MHz Channel (Port 3)		
Frequency Band	2500-2690 MHz	
Insertion Loss (Port 3 to Port 4)	≤ 0.7 dB	
Isolation	≥ 80 dB	
VSWR	≤ 1.25	
Continuous Average Power	250 W	
IM3, 2x43 dBm	< -160 dBc	
Environmental		
Temperature Range	-20° to +65° C	-4° to 149° F
Ingress Protection	IP67	
Lightning Protection	3 kA 10/350 μs	
Humidity	5-97%	
Application	Outdoor	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

TPX-23x-CC

Triplexer | 1710-1880 / 1920-2170 / 2500-2690 MHz | Single and Twin Units | Outdoor

Mechanical Characteristics			
Connectors		7/16-DIN Female	
Dimensions (H x W x D) Without Connectors or Mounting Brackets	Single Unit	243 x 195 x 55 mm	9.6 x 7.7 x 2.2 in
Weight	Single Unit	4.5 kg	9.9 lbs
Mounting Options			
Pole / Wall Bracket (included)			

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.