




UNICELL Enclosures

Enclosure Family	Diameter	Applications / Features	UNICELL Model Number		
			1830 mm (72 inch)	2435 mm (96 inch)	2745 mm (108 inch)
UNICELL 20	511 mm (20.1 inch)	<ul style="list-style-type: none"> All frequency bands ±30° azimuth* 4° mechanical tilt 	UNX20-14	UNX20-19	UNX20-25

* Feature is available in certain antenna and UNICELL combinations only. Please refer to individual antenna datasheets for full application and features.

UNICELL Accessories

Accessory	Description	Accessory Part Number
	<p>Lightning Protection Kit 18-inch (460 mm) copper air finial with a 20 ft (6 m) section of #4 AWG braided copper cable pre-attached. The kit provides all necessary hardware for installation</p>	UNX-LPK
	<p>Mounting Mast Interface flange welded to a 10 ft (3 m) steel mast pipe. The mast can be used with standard wall or pipe mounting kits to provide an inexpensive mounting system. Custom lengths are available upon request</p>	UNX20-M-120
	<p>Cable Access Canister Steel construction with same diameter and appearance as UNICELL structure to simplify cable installation and weatherproofing</p>	UNX20-C

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.