20-Port Panel Antenna

(2x) 696-896 | (4x) 1695-2700 | (4x) 3300-4200 MHz

45° | 54.8 IN | FIXED TILT

2C4U4VX045X14Fwxys5

Features

- Unique high port count panel antenna for 4G/5G small cell applications
- 20 total connectors to service the 696-896, 1695-2700 and 3300-4200 MHz bands
- Ideal for multi-carrier or 4x4 MIMO deployments
- Fixed tilt options

PRODUCT OVERVIEW			
Frequency Range (MHz)	(2x) 696-896	(4x) 1695-2700	(4x) 3300-4200
Array	R1, R2	Y1, Y2, Y3, Y4	P1, P2, P3, P4
Connector	4 PORTS	8 PORTS	8 PORTS
Polarization	XPOL	XPOL	XPOL
Azimuth Beamwidth (avg)	45°	45°	45°
Electrical Downtilt	0°	0°, 5°	0°, 5°
Maximum Continuous Power Per Port @ 50° C (122° F)	500 WATTS	300 WATTS	100 WATTS
Maximum Total Continuous Power at 50° C (122° F)	5200 WATTS		
Total Connector Count	20 PORTS		
Connector Type	4.3-10 FEMALE		
Dimensions	1392 x 407 x 179 mm (54.8 x 16.0 x 7.1)		
Radome Color Options	GREY		

ELECTRICAL SPECIFICATIONS

			R1	R2
Frequency Range		MHz	(2x) 696-896	
Frequency Sub-Range		MHz	696-806	806-896
Polarization		---	(2x) ±45°	
Gain	BASTA	dBi	12.4 ± 0.6	13.3 ± 0.5
	MAX	dBi	13.0	13.8
Azimuth Beamwidth (3 dB)		degrees	46.4° ± 2.1°	41.8° ± 3.1°
Elevation Beamwidth (3 dB)		degrees	41.1° ± 3.9°	36.1° ± 3.2°
Electrical Downtilt		degrees	(w) 0°	
Impedance		Ohms	50Ω	
VSWR		---	1.5:1	
Passive Intermodulation 3rd Order for 2x20 W Carriers		dBc	< -153	
Upper Sidelobe Suppression		dB	N/A	
Isolation	Intraband	dB	> 22	
	Interband	dB	> 28 same band; > 30 different band	

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

ELECTRICAL SPECIFICATIONS			Y1	Y2	Y3	Y4
Frequency Range		MHz	(4x) 1695-2700			
Frequency Sub-Range		MHz	1695-1880	1850-1990	1920-2200	2300-2700
Polarization		---	(4x) ±45°			
Gain	BASTA	dBi	14.1 ± 0.5	14.8 ± 0.4	15.3 ± 0.7	15.9 ± 0.5
	MAX	dBi	14.6	15.2	16.0	16.4
Azimuth Beamwidth (3 dB)		degrees	55.1° ± 7.4°	47.0° ± 5.1°	43.6° ± 6.3°	37.8° ± 5.4°
Elevation Beamwidth (3 dB)		degrees	20.7° ± 1.1°	20.0° ± 1.1°	18.9° ± 2.0°	16.3° ± 1.3°
Electrical Downtilt		degrees	(x) 0°, 5°			
Impedance		Ohms	50Ω			
VSWR		---	1.5:1			
Passive Intermodulation 3rd Order for 2x20 W Carriers		dBc	< -153			
Upper Sidelobe Suppression		dB	N/A			
Isolation	Intraband	dB	> 22			
	Interband	dB	> 28 same band; > 30 different band			

ELECTRICAL SPECIFICATIONS			P1	P2	P3	P4
Frequency Range		MHz	(4x) 3300-4200			
Frequency Sub-Range		MHz	3300-3550	3550-3700	3700-4200	
Polarization		---	(4x) ±45°			
Gain	BASTA	dBi	17.9 ± 0.6	18.3 ± 0.5	18.2 ± 0.7	
	MAX	dBi	18.5	18.8	18.9	
Azimuth Beamwidth (3 dB)		degrees	43.3° ± 6.9°	38.3° ± 5.6°	34.5° ± 5.6°	
Elevation Beamwidth (3 dB)		degrees	10.8° ± 0.4°	10.4° ± 0.4°	9.6° ± 0.6°	
Electrical Downtilt		degrees	(y) 0°, 5°			
Impedance		Ohms	50Ω			
VSWR		---	1.5:1			
Passive Intermodulation 3rd Order for 2x20 W Carriers		dBc	< -153			
Upper Sidelobe Suppression		dB	> 13.8			
Isolation	Intraband	dB	> 25			
	Interband	dB	> 28 same band; > 30 different band			

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

MECHANICAL SPECIFICATIONS

Antenna	Length		mm (in)	1392 (54.8)
	Width		mm (in)	407 (16.0)
	Depth		mm (in)	179 (7.1)
Net Weight - Antenna Only			kg (lbs)	16.3 (36)
Windload		Calculation	km/h (mph)	160 (100)
		Frontal	N (lbf)	792 (178)
		Side	N (lbf)	361 (81)
Survival Wind Speed			km/h (mph)	241 (150)
Connector		Type	---	4.3-10 Female
		Quantity	---	20
		Position	---	Bottom
Radome Color			---	Grey
Operating Temperature			degrees	-40 to +60 C (-40 to +140 F)
Lightning Protection (Grounding Type)			---	Direct Ground



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

ARRAY LAYOUT Topology

FREQUENCY	ARRAY	CONNECTOR	CONNECTOR TYPE
696-896 MHz	R1	1-2	(2x) 4.3-10 Female
696-896 MHz	R2	3-4	(2x) 4.3-10 Female
1695-2700 MHz	Y1	5-6	(2x) 4.3-10 Female
1695-2700 MHz	Y2	7-8	(2x) 4.3-10 Female
1695-2700 MHz	Y3	9-10	(2x) 4.3-10 Female
1695-2700 MHz	Y4	11-12	(2x) 4.3-10 Female
3300-4200 MHz	P1	13-14	(2x) 4.3-10 Female
3300-4200 MHz	P2	15-16	(2x) 4.3-10 Female
3300-4200 MHz	P3	17-18	(2x) 4.3-10 Female
3300-4200 MHz	P4	19-20	(2x) 4.3-10 Female



The illustration is not shown to scale.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

BOTTOM VIEW - LABELING

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

BOTTOM VIEW - CONNECTOR DIAGRAM



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

MOUNTING KITS Select from the following mounting options when ordering.

MODEL NUMBER	DESCRIPTION	FITS PIPE DIAMETER	WEIGHT
36210006 	2-POINT, SCISSOR TILT, MOUNTING & DOWNTILT BRACKET KIT	40-115 mm (1.57-4.5 in)	4.1 kg (9 lbs)

INSTALLATION Please read all installation notes before installing this product.

⚠	Always attach the antenna using all mounting points.
	Do not install the antenna with the connectors facing upwards.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

HOW TO READ THE MODEL NUMBER Each letter and number has meaning.

NUMBER OF BANDS and OPERATING FREQUENCY			PATTERN TYPE	AZIMUTH BMWDTH	POLARIZA-TION	LENGTH	TILT TYPE	TILT OPTIONS	CONNECTOR TYPE	VARIATION	ORDERING OPTION
2C	4U	4V	X	045	X	14	F	wxy	s	5	-T
(2x) 696-896	(4x) 1695-2700	(4x) 3300-4200	Standard Panel Antenna	45°	XPOL	1.4 meters	Fixed Tilt	These letters are placeholders for fixed tilt options. Refer to Electrical Specifications for available tilt options.	4.3-10 Connector	5th generation mechanical package	To order the antenna and mounting kit together as one line item, add a -T for the 2-POINT, SCISSOR TILT, MOUNTING & DOWNTILT BRACKET KIT (36210006) to the end of the model number. If -T is not added, the bracket kit can be added as a separate line item, or the antenna shipped without a bracket. Refer to the ordering options on the following page for further detail.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

ORDERING OPTIONS Select from the following ordering options

SELECT MOUNTING KIT	SELECT DEGREE OF ELECTRICAL DOWNTILT FOR EACH BAND			ORDER MODEL NUMBER
	696-896 MHz	1695-2700 MHz	3300-4200 MHz	
ANTENNA ONLY - NO MOUNTING KIT	0°	0°	0°	2C4U4VX045X14F000s5
	0°	0°	5°	2C4U4VX045X14F005s5
	0°	5°	0°	2C4U4VX045X14F050s5
	0°	5°	5°	2C4U4VX045X14F055s5
ANTENNA WITH **36210006** MOUNTING KIT 2-Point, Scissor Tilt, Mounting & Downtilt Bracket Kit	0°	0°	0°	2C4U4VX045X14F000s5-T
	0°	0°	5°	2C4U4VX045X14F005s5-T
	0°	5°	0°	2C4U4VX045X14F050s5-T
	0°	5°	5°	2C4U4VX045X14F055s5-T

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

750 MHz
850 MHz

R1, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

R2, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

1800 MHz
1900 MHz
2100 MHz
2300 MHz
2600 MHz

Y1, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y2, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y3, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y4, 0° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

1800 MHz
1900 MHz
2100 MHz
2300 MHz
2600 MHz

Y1, 5° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y2, 5° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y3, 5° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Y4, 5° TILT

+45°



Azimuth



Elevation

-45°



Azimuth



Elevation

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

3600 MHz
4000 MHz

P1, 0° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P2, 0° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P3, 0° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P4, 0° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

2C4U4VX045X14Fwxys5

3600 MHz
4000 MHz

P1, 5° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P2, 5° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P3, 5° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

P4, 5° TILT

+45°


Azimuth


Elevation

-45°


Azimuth


Elevation

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.