


## 5661310Em

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2683 mm

- Quad band antenna, dual polarisation, 8 connectors
- Independent tilt on each band 0-10° / 0-10° / 0-10° / 0-10°
- MET and RET versions, 3GPP/AISG2.0, in multiple single RET (multiple device type1) or in Multi-RET (device type 17, with firmware above MD3.10).
- Our patented, RET module controlling all tilt angles, fully inserted inside the antenna (field replaceable)

<b>PRODUCT OVERVIEW</b>	Frequency Range (MHz)	698-960	698-960	1695-2690	1695-2690
	Array	<span style="color: red;">■</span> R1	<span style="color: red;">■</span> R2	<span style="color: yellow;">■</span> Y1	<span style="color: yellow;">■</span> Y2
	Connector	1-2	3-4	5-6	7-8
	Polarization	XPOL	XPOL	XPOL	XPOL
	Azimuth Beamwidth (avg)	65°	65°	65°	65°
	Electrical Downtilt	0-10°	0-10°	0-10°	0-10°
	Dimensions	2683 x 472 x 205 mm			



### ORDERING OPTIONS

Select from the different options listed below

SELECT ELECTRICAL DOWNTILT CONTROL & AISG PROTOCOL	SELECT ACTUATOR	SELECT CONNECTOR TYPE	ANTENNA MODEL NUMBER
Manual Electrical Tilt (MET)	---	4.3-10 Female	5661310ENm
		7/16 DIN Female	5661310Em
Remote Electrical Tilt (RET) AISG v2.0 / 3GPP	Multi-Device Control Unit (MDCU)	4.3-10 Female	5661310ENGm
		7/16 DIN Female	5661310EGm



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 5661310Em

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2683 mm

### ELECTRICAL SPECIFICATIONS Low Band

■ R1, R2

Frequency Range		MHz	698-960			
		MHz	698-806	790-862	824-894	880-960
Polarization		---	± 45°			
Gain	Over all Tilts	dBi	15.3 ± 0.4	15.8 ± 0.3	15.8 ± 0.5	16.0 ± 0.4
Azimuth Beamwidth		degrees	62.2 ± 6.0	64.3 ± 5.0	66.7 ± 3.2	66.3 ± 3.5
Elevation Beamwidth		degrees	8.3 ± 0.4	7.4 ± 0.3	7.3 ± 0.3	6.9 ± 0.4
Electrical Downtilt		degrees	0-10			
Impedance		Ohms	50			
VSWR		---	< 1.5			
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -150			
Front-to-Back Ratio, ±180°		dB	> 25			
First Upper Sidelobe Suppression		dB	> 14.3	> 15.6	> 16.4	> 17.0
Cross Polar Ratio	Main Direction (0°)	dB	> 17.0	> 17.0	> 18.0	> 18.0
	Sector Edges (60°)	dB	> 10.2	> 10.7	> 10.4	> 10.7
Maximum Effective Power Per Port		Watts	300			
Inter/Intra Band Isolation		dB	> 27			

Standard values based on NGMN-P-BASTA version 12.0 recommendation.

### ELECTRICAL SPECIFICATIONS Ultra Wide Band

■ Y1, Y2

Frequency Range		MHz	1695-2690				
		MHz	1695-1880	1850-1990	1920-2180	2300-2500	2500-2690
Polarization		---	± 45°				
Gain	Over all Tilts	dBi	17.0 ± 0.7	17.2 ± 0.5	17.2 ± 0.4	17.7 ± 0.3	17.7 ± 0.5
Azimuth Beamwidth		degrees	65 ± 3.2	63 ± 1.6	63 ± 3.4	64 ± 3.7	66 ± 3.3
Elevation Beamwidth		degrees	7.2 ± 0.5	6.6 ± 0.3	6.2 ± 0.4	5.4 ± 0.3	5.0 ± 0.3
Electrical Downtilt		degrees	0-10				
Impedance		Ohms	50				
VSWR		---	< 1.5				
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -150				
Front-to-Back Ratio, ±180°		dB	> 26	> 27	> 27	> 27	> 27
First Upper Sidelobe Suppression		dB	> 17	> 17	> 17	> 17	> 17
Cross Polar Ratio	Main Direction (0°)	dB	> 15	> 15	> 16	> 17	> 15
	Sector Edges (60°)	dB	> 11.5	> 9.8	> 6.5	> 6.2	> 6.0
Maximum Effective Power Per Port		Watts	250	250	250	250	200
Inter/Intra Band Isolation		dB	> 28				

Standard values based on NGMN-P-BASTA version 12.0 recommendation.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 5661310Em

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2683 mm

### ELECTRICAL DOWNTILT CONTROL

For multiband antennas, electrical downtilt for each band can be controlled separately.

Manual Electrical Tilt (MET) Control	The MET is a separate kit provided on the bottom of the antenna. This kit has colored knobs with a respective array identification indicated within it. This knob can be rotated to set an electrical downtilt as per the requirement. The tilt information of the respective arrays can be observed with an indicator provided near the knob.
Remote Electrical Tilt (RET) Control	The remote control of the electrical tilt is managed by single RET unit inserted in the bottom of the antenna. See <i>details below and refer to the ordering options to see which actuators are available with this particular antenna</i> . A single actuator individually controls the tilt of each band (no need for daisy chain cables between the bands). This module does not add any additional length to the antenna.

### RET ACTUATOR

Amphenol's **RET-READY** antennas are delivered with the RET Actuator already installed and pre-commissioned with all antenna parameters. Every RET device is factory configured and calibrated so the antenna is ready to be used once delivered to the site which means that there is no need for further installation of RET devices.

Number of RET-READY Actuators	One per antenna	
Input Voltage	+10 to +30 V	
Power Consumption	Idle State	0.5 W
	Operating	4 W typical / 10 W maximum
Protocol	3GPP/AISG 2.0	
Tilt Change Duration	Less than 15 seconds, typical (may vary dependent on antenna type and outdoor temperature)	
Precision	± 0.5°	
Tilt Change Capability	50,000 minimum	
RET Interface	1 pair of AISG Male and Female (type IEC60130-9)	
Field Replaceable Unit	Yes	

### ENVIRONMENTAL SPECIFICATIONS

Environmental	---	ETS 300 019
Operating Temperature	° C (° F)	-40° to +60° (-40° to +140°)
Product Environmental Compliance	---	Product is RoHs Compliant

**ACCESSORIES** All accessories are ordered separately unless otherwise indicated

ITEM	MODEL NUMBER	WEIGHT
Brackets for pole Ø48 to Ø115 mm (Ø1.9 to Ø4.5 in) <b>delivered as standard</b>	IA00181	3.4 kg (7.5 lbs)
Kit to add mechanical tilt (0° to 10°) to above brackets <b>optional</b>	0900397/00	3.0 kg (6.6 lbs)

**INSTALLATION** Please read all installation notes before installing this product.




Always attach the antenna by all mounting points.

Do not install the antenna with the connectors facing upwards.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 5661310Em

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2683 mm



ARRAY LAYOUT	ARRAY	FREQUENCY	CONNECTOR	CONNECTOR TYPE
	<span style="color: red;">■</span> R1	698-960	1-2	4.3-10 Female or 7/16 DIN Female Long Neck
	<span style="color: red;">■</span> R2	698-960	3-4	4.3-10 Female or 7/16 DIN Female Long Neck
	<span style="color: yellow;">■</span> Y1	1695-2690	5-6	4.3-10 Female or 7/16 DIN Female Long Neck
	<span style="color: yellow;">■</span> Y2	1695-2690	7-8	4.3-10 Female or 7/16 DIN Female Long Neck

Diagram shown at right depicts the view from the front of the antenna. The illustration is not shown to scale.

### MECHANICAL SPECIFICATIONS

Length	mm (in)	2683 (105.6)	
Width	mm (in)	472 (18.5)	
Depth	mm (in)	205 (8.0)	
Net Weight - Antenna Only	kg (lbs)	38 (83.7)	
Mechanical Distance Between Mounting Points	mm (in)	1865 (73.4)	
Windload (EN 1991-1-4:2005 using Wind Tunnel Coefficients)	Calculation	km/h (mph)	150 (93.2)
	Frontal	N (lbf)	1329 (298.7)
	Lateral	N (lbf)	373 (83.8)
	Rearside	N (lbf)	1446 (325.0)
Operational Wind Speed	km/h (mph)	160 (99.4)	
Survival Wind Speed	km/h (mph)	225 (139.8)	
Radome Color	---	Gray RAL7035	
Radome Material	---	Outdoor Fibreglass	
Lightning Protection	---	Direct Ground	
Shipping	Shipping Dimensions (Length x Width x Depth)	mm (in)	2883 x 613 x 370 (113.5 x 24.1 x 14.5)
	Shipping Weight	kg (lbs)	57 (125.6)
	Shipping Volume	m <sup>3</sup> (ft <sup>3</sup> )	0.65 (15.9)

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.