

6888370






6888370N 6888370G 6888370NG


5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

- Penta band, dual polarisation, 10 connectors
- Independent tilt on each band 2-12° / 2-12° / 0-10° / 0-10° / 0-10°
- UltraLine platform with multi-array capability
- MET and RET versions, 3GPP/AISG2.0
- Our patented, RET module controlling all tilt angles, fully inserted inside the antenna (field replaceable)

UltraLine

LTE Ready

PRODUCT OVERVIEW	Frequency Range (MHz)	698-788	880-960	1695-2180	1695-2690	2490-2690
	Array	 R1	 R2	 B1	 Y1	 Y2
	Connector	1-2	3-4	5-6	7-8	9-10
	Polarization	XPOL	XPOL	XPOL	XPOL	XPOL
	Azimuth Beamwidth (avg)	65°	65°	65°	65°	65°
	Electrical Downtilt	2-12°	2-12°	0-10°	0-10°	0-10°
	Dimensions	1914 x 305 x 162 mm				



ORDERING OPTIONS

Select from the different options listed below

SELECT ELECTRICAL DOWNTILT CONTROL & AISG PROTOCOL	SELECT ACTUATOR	SELECT CONNECTOR TYPE	ANTENNA MODEL NUMBER
Manual Electrical Tilt (MET)	---	4.3-10 Female	6888370N
		7/16-DIN Female	6888370
Remote Electrical Tilt (RET) AISG v2.0 / 3GPP	Multi-Device Control Unit (MDCU)	4.3-10 Female	6888370NG
		7/16-DIN Female	6888370G

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

ELECTRICAL SPECIFICATIONS Ultra Low Band

R1

Frequency Range		MHz	698-788
Polarization		---	±45°
Gain	Min Tilt	dBi	14.8
	Mid Tilt	dBi	14.8
	Max Tilt	dBi	14.5
Azimuth Beamwidth		degrees	73°
Elevation Beamwidth		degrees	12°
Electrical Downtilt		degrees	2°-12°
Impedance		Ohms	50
VSWR		---	< 1.5
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110
Front-to-Back Ratio, Total Power, ±30°		dB	> 25
Upper Sidelobe Suppression, 0° to 20°		dB	18 typical
Maximum Effective Power Per Port		Watts	250 W
Inter/Intra Band Isolation		dB	> 25

ELECTRICAL SPECIFICATIONS Ultra Low Band

R2

Frequency Range		MHz	880-960
Polarization		---	±45°
Gain	Min Tilt	dBi	16.0
	Mid Tilt	dBi	15.9
	Max Tilt	dBi	15.6
Azimuth Beamwidth		degrees	67°
Elevation Beamwidth		degrees	9.4°
Electrical Downtilt		degrees	2°-12°
Impedance		Ohms	50
VSWR		---	< 1.5
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110
Front-to-Back Ratio, Total Power, ±30°		dB	> 25
Upper Sidelobe Suppression, 0° to 20°		dB	18 typical
Maximum Effective Power Per Port		Watts	250 W
Inter/Intra Band Isolation		dB	> 25

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

ELECTRICAL SPECIFICATIONS Filtered Array (Y2)

■ B1

Frequency Range		MHz	1695-2180	
		MHz	1800	2100
Polarization		---	±45°	
Gain	Min Tilt	dBi	17.2	17.5
	Mid Tilt	dBi	17.2	17.4
	Max Tilt	dBi	17.1	17.3
Azimuth Beamwidth		degrees	65°	65°
Elevation Beamwidth		degrees	6.1°	5.3°
Electrical Downtilt		degrees	0°-10°	
Impedance		Ohms	50	
VSWR		---	< 1.5	
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110	
Front-to-Back Ratio, Total Power, ±30°		dB	> 25	
Upper Sidelobe Suppression, 0° to 20°		dB	18 typical	
Maximum Effective Power Per Port		Watts	200 W	
Inter/Intra Band Isolation		dB	> 28	

ELECTRICAL SPECIFICATIONS Ultra Wide Band

■ Y1

Frequency Range		MHz	1695-2690		
		MHz	1800	2100	2600
Polarization		---	±45°		
Gain	Min Tilt	dBi	17.5	17.7	17.9
	Mid Tilt	dBi	17.5	17.7	17.8
	Max Tilt	dBi	17.4	17.6	17.5
Azimuth Beamwidth		degrees	68°	70°	72°
Elevation Beamwidth		degrees	6.1°	5.3°	4.2°
Electrical Downtilt		degrees	0°-10°		
Impedance		Ohms	50		
VSWR		---	< 1.5		
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110		
Front-to-Back Ratio, Total Power, ±30°		dB	> 25		
Upper Sidelobe Suppression, 0° to 20°		dB	18 typical		
Maximum Effective Power Per Port		Watts	200 W		
Inter/Intra Band Isolation		dB	> 25		

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

ELECTRICAL SPECIFICATIONS Filtered Array (B1)

 **Y2**

Frequency Range		MHz	2490-2690
Polarization		---	±45°
Gain	Min Tilt	dBi	17.6
	Mid Tilt	dBi	17.5
	Max Tilt	dBi	17.2
Azimuth Beamwidth		degrees	65°
Elevation Beamwidth		degrees	4.2°
Electrical Downtilt		degrees	0°-10°
Impedance		Ohms	50
VSWR		---	< 1.5
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBm	< -110
Front-to-Back Ratio, Total Power, ±30°		dB	> 25
Upper Sidelobe Suppression, 0° to 20°		dB	18 typical
Maximum Effective Power Per Port		Watts	200 W
Inter/Intra Band Isolation		dB	> 28

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

ELECTRICAL DOWNTILT CONTROL

For multiband antennas, electrical downtilt for each band can be controlled separately. Tilt indicator(s) are covered by removable transparent cap(s).

Manual Electrical Tilt (MET) Control

A colored knob at the end of the tilt indicator allows change of the tilt without need of a tool. The knob color is identical to the corresponding connector color. To access the knob, remove the cap by turning it counter-clockwise. It is re-installed by opposite rotation. **Do not remove the transparent cap(s) from the antenna.**

Remote Electrical Tilt (RET) Control

The remote control of the electrical tilt is managed by a Multi-Device Control Unit (MDCU) or a Multi-Device Dual Unit (MDDU) inserted in the bottom of the antenna. *See details below and refer to the ordering options to see which actuators are available with this particular antenna.* A single actuator individually controls the tilt of each band (no need for daisy chain cables between the bands). This module does not add any additional length to the antenna. For RET control, the transparent caps must be in place and locked. The tilt angle indicators always remain visible and the antenna still has manual tilt control (manual override). **Do not remove the transparent cap(s) from the antenna.**

RET ACTUATOR

Amphenol's **RET-READY** antennas are delivered with the RET Actuator already installed and pre-commissioned with all antenna parameters. Every RET device is factory configured and calibrated so the antenna is ready to be used once delivered to the site which means that there is no need for further installation of RET devices or for programming their configuration or for running a calibration process.

RET-READY ACTUATORS

Multi-Device Control Unit (MDCU). The MDCU is an electronic module that allows the remote control of the electrical downtilt (RET) in Amphenol antennas with factory embedded motors. The MDCU is factory installed. *Refer to the ORDERING OPTIONS for availability with this model*

Multi-Device Dual Unit (MDDU). The MDDU allows two separate RET Controllers to independently drive the RETs in antennas with factory embedded motors (for antenna sharing or two technologies). The MDDU is factory installed. *Refer to the ORDERING OPTIONS for availability with this model.*

Number of RET-READY Actuators		One per antenna
Input Voltage		+10 to +30 V
Power Consumption	Idle State	0.5 W
	Operating	4 W typical / 10 W maximum
Protocol		3GPP/AISG 2.0
Tilt Change Duration		Less than 15 seconds, typical (may vary dependent on antenna type and outdoor temperature)
Precision		±0.5°
Tilt Change Capability		50,000 minimum
RET Interface		1 pair of AISG Male and Female (type IEC60130-9)
Field Replaceable Unit		Yes

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm



ARRAY LAYOUT	ARRAY	FREQUENCY	CONNECTOR	CONNECTOR TYPE
	R1	698-788	1-2	4.3-10 Female or 7/16-DIN Female Long Neck
	R2	880-960	3-4	4.3-10 Female or 7/16-DIN Female Long Neck
	B1	1695-2180	5-6	4.3-10 Female or 7/16-DIN Female Ultra Long Neck
	Y1	1695-2690	7-8	4.3-10 Female or 7/16-DIN Female Ultra Long Neck
	Y2	2490-2690	9-10	4.3-10 Female or 7/16-DIN Female Long Neck




Diagram shown at right depicts the view from the front of the antenna.
The illustration is not shown to scale.

MECHANICAL SPECIFICATIONS

Length		mm (in)	1914 (75.4)
Width		mm (in)	305 (12.0)
Depth		mm (in)	162 (6.4)
Net Weight - Antenna Only		kg (lbs)	31 (68.3)
Mechanical Distance Between Mounting Points		mm (in)	Refer to Diagram
Windload (EN 1991-1-4:2005 using Wind Tunnel Coefficients)	Calculation	km/h (mph)	150 (93.2)
	Frontal	N (lbf)	764 (171.8)
	Lateral	N (lbf)	348 (78.2)
	Rearside	N (lbf)	749 (168.4)
Operational Wind Speed		km/h (mph)	160 (99.4)
Survival Wind Speed		km/h (mph)	200 (124.3)
Radome Color		---	Gray RAL7035
Radome Material		---	Outdoor Plastic
Lightning Protection		---	Direct Ground
Shipping	Shipping Dimensions (Length x Width x Depth)	mm (in)	2170 x 400 x 280 (85.4 x 15.7 x 11.0)
	Shipping Weight	kg (lbs)	41 (90.4)
	Shipping Volume	m ³ (ft ³)	0.243 (8.6)

6888370

6888370N 6888370G 6888370NG

5-Band, 10-Port, 65°, XPOL, Panel Antenna, Variable Tilt, UltraLine, 1914 mm

ENVIRONMENTAL SPECIFICATIONS

Environmental	---	ETS 300 019
Operating Temperature	° C (° F)	-40° to +60° (-40° to +140°)
Product Environmental Compliance	---	Product is RoHS Compliant

ACCESSORIES

All accessories are ordered separately unless otherwise indicated

ITEM	MODEL NUMBER	WEIGHT
Brackets for pole Ø48 to Ø115 mm (Ø1.9 to Ø4.5 in) delivered as standard	0900181/00	3.4 kg (7.5 lbs)
Brackets for pole Ø70 to Ø150 mm (Ø2.8-Ø5.9 in) optional	0900182/00	3.9 kg (8.6 lbs)
Kit to add mechanical tilt (0° to 10°) to above brackets optional	0900397/00	3.0 kg (6.6 lbs)

Wall mounting brackets are available upon request

INSTALLATION

Please read all installation notes before installing this product.




Always attach the antenna by all mounting points.

Do not install the antenna with the connectors facing upwards.

Do not cut the tethered transparent cap(s) that cover the antenna's tilt adjustment indicators.

In order to operate the RET control, the transparent caps covering the tilt adjustment indicators must be engaged and locked.

Dimensions shown in mm



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.