

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm

- Quad band antenna, dual polarisation, 8 connectors
- Independent tilt on each band 0-10° / 2-12° / 2-12° / 2-12°
- UltraLine platform with multi-array capability
- MET and RET versions, 3GPP/AISG2.0
- Single RET module to control all tilt angles, fully inserted inside the antenna (field replaceable)

StreamLine



PRODUCT OVERVIEW	Frequency Range (MHz)	698-960	1695-2690	1695-2690	1695-2690
	Array	<span style="color: red;">■</span> R1	<span style="color: yellow;">■</span> Y1	<span style="color: yellow;">■</span> Y2	<span style="color: yellow;">■</span> Y3
	Connector	1-2	3-4	5-6	7-8
	Polarization	XPOL	XPOL	XPOL	XPOL
	Azimuth Beamwidth (avg)	65°	65°	65°	65°
	Electrical Downtilt	0-10°	2-12°	2-12°	2-12°
	Dimensions	2691 x 398 x 159 mm			

### ELECTRICAL SPECIFICATIONS Ultra Low Band

■ R1

Frequency Range		MHz	698-960			
		MHz	698-806	790-862	824-894	880-960
Polarization		---	±45°			
Gain	Over all Tilts	dBi	15.5 ± 0.4	15.8 ± 0.6	16.8 ± 0.2	16.8 ± 0.5
Azimuth Beamwidth		degrees	67.0° ± 5.0°	68.0° ± 1.8°	67.0° ± 2.3°	66.0° ± 5.0°
Elevation Beamwidth		degrees	9.3° ± 0.9°	8.5° ± 0.4°	7.5° ± 0.4°	7.6° ± 0.9°
Electrical Downtilt		degrees	0°-10°			
Impedance		Ohms	50			
VSWR			< 1.5			
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -153			
Front-to-Back Ratio, Total Power, ±30°		dB	> 25.2	> 26.4	> 25.7	> 25.1
Upper Sidelobe Suppression	First Upper Lobe	dB	> 16.0	> 16.0	> 16.0	> 16.0
	Peak to 20°	dB	> 15.0	> 15.0	> 15.0	> 15.0
Cross Polar Ratio	Main Direction (0°)	dB	> 18.0	> 18.6	> 19.3	> 17.8
	Sector Edges (60°)	dB	> 13.0	> 12.8	> 12.1	> 8.6
Maximum Effective Power Per Port		Watts	500 W			
Inter/Intra Band Isolation		dB	> 30 / > 26			
Cross-Polar Isolation		dB	> 16			

Standard values based on NGMN-P-BASTA version 10.0 recommendation.



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm

### ELECTRICAL SPECIFICATIONS Ultra Wide Band

Y1

Frequency Range		MHz	1695-2690				
		MHz	1695-1880	1850-1990	1920-2180	2300-2500	2490-2690
Polarization			±45°				
Gain	Over all Tilts	dBi	16.5 ± 0.5	16.9 ± 0.4	17.0 ± 0.5	17.8 ± 0.4	17.5 ± 0.5
Azimuth Beamwidth		degrees	65.0° ± 5.0°	64.2° ± 6.5°	65.0° ± 5.0°	63.5° ± 2.7°	64.0° ± 5.0°
Elevation Beamwidth		degrees	7.0° ± 0.7°	6.6° ± 0.4°	6.0° ± 0.6°	5.4° ± 0.2°	5.0° ± 0.5°
Electrical Downtilt		degrees	2°-12°				
Impedance		Ohms	50				
VSWR			< 1.5				
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -153				
Front-to-Back Ratio, Total Power, ±30°		dB	> 26.0	> 27.5	> 28.2	> 25.1	> 26.1
Upper Sidelobe Suppression	First Upper Lobe	dB	> 17.2	> 17.4	> 16.7	> 17.3	> 16.0
	Peak to 20°	dB	> 16.2	> 16.4	> 15.7	> 16.3	> 15.0
Cross Polar Ratio	Main Direction (0°)	dB	> 20.6	> 20.1	> 21.7	> 19.5	> 18.7
	Sector Edges (60°)	dB	> 8.0	> 9.7	> 9.7	> 8.0	> 7.2
Maximum Effective Power Per Port		Watts	250 W				
Inter/Intra Band Isolation		dB	> 30 / > 27				
Cross-Polar Isolation		dB	> 16				

Standard values based on NGMN-P-BASTA version 10.0 recommendation.

### ELECTRICAL SPECIFICATIONS Ultra Wide Band

Y2

Frequency Range		MHz	1695-2690				
		MHz	1695-1880	1850-1990	1920-2180	2300-2500	2490-2690
Polarization			±45°				
Gain	Over all Tilts	dBi	16.5 ± 0.5	15.8 ± 0.4	17.0 ± 0.5	16.7 ± 0.5	17.5 ± 0.5
Azimuth Beamwidth		degrees	65.0° ± 5.0°	65.0° ± 6.1°	65.0° ± 5.0°	63.1° ± 2.3°	64.0° ± 5.0°
Elevation Beamwidth		degrees	7.0° ± 0.7°	7.3° ± 0.5°	6.0° ± 0.6°	5.4° ± 0.2°	5.0° ± 0.5°
Electrical Downtilt		degrees	2°-12°				
Impedance		Ohms	50				
VSWR		---	< 1.5				
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -153				
Front-to-Back Ratio, Total Power, ±30°		dB	> 27.6	> 26.3	> 26.6	> 29.0	> 27.0
Upper Sidelobe Suppression	First Upper Lobe	dB	> 17.7	> 16.4	> 16.2	> 16.3	> 16.0
	Peak to 20°	dB	> 16.7	> 15.4	> 15.2	> 15.3	> 15.0
Cross Polar Ratio	Main Direction (0°)	dB	> 19.0	> 21.8	> 22.0	> 22.9	> 18.3
	Sector Edges (60°)	dB	> 10.2	> 11.5	> 11.0	> 9.4	> 8.2
Maximum Effective Power Per Port		Watts	250 W				
Inter/Intra Band Isolation		dB	> 30 / > 27				
Cross-Polar Isolation		dB	> 16				

Standard values based on NGMN-P-BASTA version 10.0 recommendation.

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm

### ELECTRICAL SPECIFICATIONS Ultra Wide Band

 **Y3**

Frequency Range		MHz	1695-2690				
		MHz	1695-1880	1850-1990	1920-2180	2300-2500	2490-2690
Polarization		---	±45°				
Gain	Over all Tilts	dBi	16.5 ± 0.5	16.8 ± 0.4	17.0 ± 0.5	17.1 ± 0.6	17.5 ± 0.5
Azimuth Beamwidth		degrees	65.0° ± 5.0°	65.7° ± 6.9°	65.0° ± 5.0°	63.5° ± 3.0°	64.0° ± 5.0°
Elevation Beamwidth		degrees	7.0° ± 0.7°	6.7° ± 0.4°	6.0° ± 0.6°	5.3° ± 0.2°	5.0° ± 0.5°
Electrical Downtilt		degrees	2°-12°				
Impedance		Ohms	50				
VSWR		---	< 1.5				
Passive Intermodulation 3rd Order for 2 x 20W Carriers		dBc	< -153				
Front-to-Back Ratio, Total Power, ±30°		dB	> 27.7	> 27.8	> 28.4	> 27.5	> 27.1
Upper Sidelobe Suppression	First Upper Lobe	dB	> 17.1	> 17.4	> 16.4	> 16.1	> 16.0
	Peak to 20°	dB	> 16.1	> 16.4	> 15.4	> 15.1	> 15.0
Cross Polar Ratio	Main Direction (0°)	dB	> 21.0	> 21.0	> 20.6	> 21.6	> 17.8
	Sector Edges (60°)	dB	> 9.1	> 11.6	> 12.3	> 8.3	> 7.0
Maximum Effective Power Per Port		Watts	250 W				
Inter/Intra Band Isolation		dB	> 30 / > 27				
Cross-Polar Isolation		dB	> 16				

Standard values based on NGMN-P-BASTA version 10.0 recommendation.

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm

### ELECTRICAL DOWNTILT CONTROL

For multiband antennas, electrical downtilt for each band can be controlled separately.

Manual Electrical Tilt (MET) Control	A colored knob at the end of the tilt indicator allows change of the tilt without need of a tool. The knob color is identical to the corresponding connector color. The manual tilt 'override' function is always available with no need to remove the physical RET motor.
Remote Electrical Tilt (RET) Control	The remote control of the electrical tilt is managed by a Multi-Device Control Unit (MDCU) or a Multi-Device Dual Unit (MDDU) or a Multi-Device Quadport Unit (MDQU) inserted in the bottom of the antenna. <i>See details below and refer to the ordering options to see which actuators are available with this particular antenna.</i> A single actuator individually controls the tilt of each band (no need for daisy chain cables between the bands). This module does not add any additional length to the antenna.



### RET ACTUATOR

Amphenol's **RET-READY** antennas are delivered with the RET Actuator already installed and pre-commissioned with all antenna parameters. Every RET device is factory configured and calibrated so the antenna is ready to be used once delivered to the site which means that there is no need for further installation of RET devices or for programming their configuration or for running a calibration process.

RET-READY ACTUATORS	Multi-Device Quadport Unit (MDQU). The MDQU allows two separate RET Controllers to independently drive the RETs in antennas with factory embedded motors (for antenna sharing or two technologies). This can be used to enable daisy-chain operation for two operators simultaneously. The MDQU is factory installed. <i>Refer to the ORDERING OPTIONS for availability with this model.</i>	
Number of RET-READY Actuators		One per antenna
Input Voltage		+10 to +30 V
Power Consumption	Idle State	0.5 W
	Operating	4 W typical / 10 W maximum
Protocol		3GPP/AISG 2.0
Tilt Change Duration		Less than 15 seconds, typical (may vary dependent on antenna type and outdoor temperature)
Lightning Protection Rating		8kA (8/20µs)
Tilt Change Capability		50,000 minimum
RET Interface		2 pair of AISG Male and Female (type IEC60130-9)
Field Replaceable Unit		Yes

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm



ARRAY LAYOUT	ARRAY	FREQUENCY	CONNECTOR	CONNECTOR TYPE
	R1	698-960	1-2	4.3-10 Female Long Neck
	Y1	1695-2690	3-4	4.3-10 Female Long Neck
	Y2	1695-2690	5-6	4.3-10 Female Long Neck
	Y3	1695-2690	7-8	4.3-10 Female Long Neck

Diagram shown at right depicts the view from the front of the antenna.  
The illustration is not shown to scale.

### MECHANICAL SPECIFICATIONS

Length		mm (in)	2691 (105.9)
Width		mm (in)	398 (15.6)
Depth		mm (in)	159 (6.2)
Net Weight - Antenna Only		kg (lbs)	34 (74.9)
Mechanical Distance Between Mounting Points		mm (in)	Refer to Diagram
Windload (Wind Tunnel Coefficients)	Calculation	km/h (mph)	150 (93.2)
	Frontal	N (lbf)	1350 (303.4)
	Lateral	N (lbf)	450 (101.1)
	Rearside	N (lbf)	1600 (359.6)
Operational Wind Speed		km/h (mph)	160 (99.4)
Survival Wind Speed		km/h (mph)	200 (124)
Radome Color		---	Gray RAL7035
Radome Material		---	FRP
Lightning Protection		---	Direct Ground
Shipping	Shipping Dimensions (Length x Width x Depth)	mm (in)	2800 x 498 x 312 (110.2 x 19.6 x 12.2)
	Shipping Weight	kg (lbs)	49 (108.0)
	Shipping Volume	m <sup>3</sup> (ft <sup>3</sup> )	0.435 (15.3)

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

## 6890300ENQv

4-Band, 8-Port, 65°, XPOL, Panel Antenna, Variable Tilt, 2691 mm

### ENVIRONMENTAL SPECIFICATIONS

Environmental Standard	---	RoHS 2011/65/EU and ISO Certification 901/2015 & 14001/2015
Operating Temperature	° C (° F)	-40° to +55° (-40° to 131°)
Product Environmental Compliance	---	Product is RoHs Compliant

### ACCESSORIES

All accessories are ordered separately unless otherwise indicated

ITEM	MODEL NUMBER	WEIGHT
Brackets for pole Ø48 to Ø115 mm (Ø1.9 to Ø4.5 in) <b>delivered as standard</b>	0900181/00	3.4 kg (7.5 lbs)
Brackets for pole Ø70 to Ø150 mm (Ø2.8-Ø5.9 in) <b>optional</b>	0900182/00	3.9 kg (8.6 lbs)
Kit to add mechanical tilt (0° to 10°) to above brackets <b>optional</b>	0900397/00	3.0 kg (6.6 lbs)

Wall mounting brackets are available upon request

### INSTALLATION

Please read all installation notes before installing this product.



Always attach the antenna by all mounting points.

Do not install the antenna with the connectors facing upwards.

