

MKS02T08 Narrow Long Scissor Downtilt Mounting Bracket Installation Instructions:

1. Attach the antenna to the **interface brackets (13)** using the provided antenna mounting channel runners. **Distance** between the brackets should be 7.07in/197.6mm, wide chassis shown. Narrow chassis installations will have the tabs facing inward.

Adjust the brackets to ensure that they are perpendicular to the antenna and spaced 1-1/2 meters (59.05) apart, approx. equal distance from top and bottom of the antenna (use placement guide labels on antenna when provided) with a maximum distance of 14" between the lower pivot point and the bottom of the antenna.

- 2. Assemble the interface brackets (13) to scissor brackets (4&14) on top half with 3/8" locking hardware. Then attach the pipe grip with mounting tabs (3) to scissor bracket assembly as shown.

 Attach the other pipe grip with mounting tabs (3) to bottom interface brackets (13) with 3/8" locking hardware.
- 3. Assemble **rear pipe grip (2)** with one bolt to front **pipe grip with mounting tabs (3)**. Raise antenna to pipe. Install second bolt in pipe grip assembly and tighten to pipe. Tighten pipe grip hardware to 15Nm (11ft lbs.)
- 4. Position the antenna in desired downtilt position. Letters on scissor bracket indicate one degree increments of mechanical down tilt A= 0 degrees. After positioning find the holes in the two scissor brackets that align and install the 1/4" locking hardware on both sides.

 Tighten all 1/4" hardware to 15Nm (11ft lbs.)

 Tighten the 3/8" hardware to 20Nm (15 ft-lbs).
- 5. Make all electrical connections and weatherproof with self-amalgamating tape.



NAME DATE DRAWN RHH 03/13/07 CHECKED ENG APPR. MFG APPR. Q.A. COMMENTS: DO NOT SCALE DRAWING SIZE DWG. NO. MKS02T08 REV. A

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF JAYBEAM WIRELESS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF JAYBEAM WIRELESS IS PROHIBITED.