

P6174300

Single Band | Panel | X-Pol | 70° | 14 dBi | Fixed Tilt

- Single band, X-Pol, fixed tilt, panel antenna
- Mounting and downtilt brackets included

Electrical Characteristics		
Frequency Bands	2400-2500 MHz	
Polarization	±45°	
Horizontal Beamwidth	70°	
Vertical Beamwidth	12°	
Gain	14 dBi	
Electrical Downtilt	0°	
Impedance	50Ω	
VSWR	≤ 1.5	
Front-to-Back Ratio	≥ 20 dB	
Isolation	≥ 20 dB	
Input Power	100 W	
Operating Temperature	-40° to +60° C (-40° to +140° F)	
Lightning Protection	DC Ground	
Connector(s)	2 / N Female / Bottom	
Mechanical Characteristics		
Dimensions (Height x Width x Depth)	500 x 160 x 80 mm	19.7 x 6.3 x 3.1 in
Weight without Mounting Brackets	4 kg	8.8 lbs
Survival Wind Speed	210 km/h	130.5 mph
Mounting Options		
	Attach to Pipe Diameter	
Mounting & Downtilt Bracket Kit Included	Ø30-Ø50 mm	Ø1.2-Ø2.0 in



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.